

ALL SIZES AND SPECS

TIRE SIZES BY WHEEL DIAMETER														
15" 16" 17" 18" 20" 22" 24" "														
7 sizes 8 sizes 12 sizes 12 sizes 15 sizes 7 sizes 1 size 2 sizes														

TIRE SIZE	PART NUMBER	LOAD I.D.	UTQG RATING	UNIT WEIGHT (lbs.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (in.)	TREAD DEPTH (32/in.)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE	TYPE
					Meas.	Appr.	Overall Width	Overall Diameter			Static Radius	Rev / Mile	Single	
35X11.50R20 124Q	110133357	E	NA	67.7	9	8.00-10.50	11.3	34.8	9.3	21	15.8	597	3525@80	BW
33X12.50R20 114Q	110133332	E	NA	64.8	10	8.5 - 11.0	12.7	32.7	10.2	21	14.9	636	2600@65	BW
33X12.50R20 119Q	110133362	F	NA	66.1	10	8.50-11.00	12.6	32.7	10.2	21	15	635	3000@80	BW
35X12.50R20 121Q	110133331	E	NA	71.2	10	8.5 - 11.0	12.6	34.7	10.2	21	15.7	598	3195@65	BW
35X12.50R20 125Q	110133359	F	NA	71.3	10	8.50-11.00	12.6	34.8	10.2	21	15.8	597	3640@80	BW
37X12.50R20 126Q	110133337	E	NA	76.7	10	8.5 - 11.0	12.8	36.7	10.2	21	16.5	566	3750@65	BW
37X13.50R20 127Q	110133334	E	NA	80.9	11	8.5 - 11.0	13.9	36.6	11.1	21	16.5	567	3860@65	BW
LT275/55R20 120/117Q	110133352	E	NA	57.5	8.5	7.50 - 9.50	10.9	32.2	9.1	19	14.7	646	3085@80	BW
LT275/65R20 126/123 Q	110133335	E	NA	64.8	8	7.5 - 9.5	11	34.3	9	19	15.6	605	3750@80	BW
LT295/55R20 123/120 Q	110133344	E	NA	63.9	9.5	8.0-10.0	12	33	9.9	20	15.1	629	3415@80	BW
LT295/60R20 126/123 Q	110133336	E	NA	66.8	8.5	8.0 - 10.0	11.7	34.1	9.6	20	15.5	609	3750@80	BW
LT295/65R20 129/126Q	110133364	E	NA	69.2	8.5	8.50-10.50	11.6	35.3	9.6	20	16	589	4080@80	BW
LT305/55R20 125/122Q	110133358	F	NA	64.9	9.5	9.00-11.00	12.4	33.5	10	20	15.3	620	3640@80	BW
LT305/55R20 121/118 Q	110133333	E	NA	65	9.5	8.5 - 11.0	12.4	33.4	10	20	15.2	622	3195@65	BW
LT315/60R20 125/122Q	110133350	D	NA	71.9	9.5	8.50 - 11.00	12.8	35	10.4	20	15.9	593	3640@65	BW