

ALL SIZES AND SPECS

TIRE SIZES BY WHEEL DIAMETER			15" 12 sizes	16" 24 sizes	17" 29 sizes	18" 22 sizes	19" 2 sizes	20" 18 sizes	22" 4 sizes					
TIRE SIZE	PART NUMBER	LOAD I.D.	UTQG RATING	UNIT WEIGHT (lbs.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (in.)	TREAD DEPTH (32/in.)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE	TYPE
					Meas.	Appr.	Overall Width	Overall Diameter			Static Radius	Rev / Mile	Single	
215/60R16 95H	110101586	SL	600/A/B	24.9	6.5	6.0 - 7.5	8.7	26.1	6.5	12	11.9	796	1521@51	BW
215/65R16 98H	110101573	SL	600/A/B	26.2	6.5	6.0 - 7.5	8.8	27	6.5	12	12.3	769	1653@51	BW
215/70R16 100H	110101574	SL	600/A/B	28.2	6.5	5.5 - 7.0	8.7	27.9	6.5	12	12.6	745	1764@51	BW
LT215/85R16 115/112R	110101630	E	NA	39.9	6	5.5 - 7.0	8.6	30.5	6.5	16	13.6	682	2680@80	OWL
225/70R16 103H	110101575	SL	600/A/B	30.3	6.5	6.0 - 7.5	9.1	28.4	6.7	12	12.8	732	1929@51	BW
LT225/75R16 115/112R	110101631	E	NA	39.2	6	6.0 - 7.0	8.7	29.4	6.9	17	13.2	705	2680@80	OWL
235/60R16 100H	110101576	SL	600/A/B	29.1	7	6.5 - 8.5	9.4	27	7.1	12	12.3	768	1764@51	BW
P235/70R16 104T	110101511	SL	600/A/B	32.4	7	6.0 - 8.0	9.3	29	7	13	13.1	716	1984@51	OWL
LT235/85R16 120/116R	110101632	E	NA	47	6.5	6.0 - 7.5	9.3	31.9	7.2	17	14.2	652	3042@80	OWL
LT245/70R16	110101679	E	NA	42.6	7	6.50-8.00	9.9	29.6	7.6	17	13.3	702	2910@80	BW
P245/70R16 106T	110101512	SL	600/A/B	34.8	7	6.5 - 8.0	9.6	29.6	7.2	13	13.3	703	2094@51	OWL
LT245/75R16 120/116S	110101633	E	NA	45.6	7	6.5 - 8.0	9.8	30.6	7.6	17	13.7	679	3042@80	OWL
P245/75R16 109T	110101513	SL	600/A/B	37.7	7	6.5 - 8.0	9.7	30.5	7.2	13	13.7	681	2271@51	OWL
255/65R16 109H	110101514	SL	600/A/B	34.8	7.5	7.0 - 9.0	10.3	29.1	7.6	12	13.1	714	2271@51	BW
LT255/70R16 115/112S	110101681	D	NA	44.3	7.5	6.50-8.50	10.4	30.2	8	17	13.5	688	2680@65	BW
P255/70R16 109T	110101515	SL	600/A/B	35.9	7.5	6.5 - 8.5	10.1	30.2	7.6	13	13.5	689	2271@51	OWL
P265/70R16 111T	110101516	SL	600/A/B	38.1	8	7.0 - 9.0	10.6	30.7	8	13	13.7	677	2403@51	OWL
LT265/75R16 123/120R	110101634	E	NA	48.7	7.5	7.00 - 8.00	10.6	31.7	8.3	18	14.1	655	3415@80	OWL
P265/75R16 114T	110101517	SL	600/A/B	41.1	7.5	7.0 - 9.0	10.6	31.7	8	13	14.1	656	2601@51	OWL
275/70R16 114H	110101577	SL	600/A/B	41.8	8	7.0 - 9.0	11	31.2	8.2	13	13.9	665	2601@51	BW
LT285/75R16 126/123R	110101635	E	NA	56.4	8	7.5 - 9.0	11.4	32.8	8.8	18	14.5	634	3750@80	OWL
LT295/75R16 128/125R	110101666	E	NA	59.5	8	7.5 - 9.5	11.6	33.7	9.1	18	14.9	617	3970@80	BW
LT305/70R16 124/121R	110101665	E	NA	56.9	9	8.0 - 9.5	12.2	33	9.6	18	14.6	630	3525@65	BW
LT315/75R16 127/124R	110101636	E	NA	64.4	8.5	8.0 - 11.0	12	34.5	9.4	18	15.2	602	3860@65	OWL