

ALL SIZES AND SPECS

TIRE SIZES BY WHEEL DIAMETER														
15" 12 sizes 16" 24 sizes 17" 29 sizes 18" 22 sizes 19" 2 sizes 20" 18 sizes 22" 4 sizes														
TIRE SIZE	PART NUMBER	LOAD I.D.	UTQG RATING	UNIT WEIGHT (lbs.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (in.)	TREAD DEPTH (32/in.)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE	TYPE
					Meas.	Appr.	Overall Width	Overall Diameter			Static Radius	Rev / Mile	Single	
215/60R17 96H	110101583	SL	600/A/B	27.1	6.5	6.0 - 7.5	8.7	27.2	6.5	12	12.5	765	1565@51	BW
215/65R17 103H	110101676	XL	600/A/B	28	6.5	6.00-7.50	8.7	28.1	6.5	12	12.8	740	1929@50	BW
225/60R17 99H	110101663	SL	600/A/B	28	6.5	6.00 - 8.00	8.9	27.7	6.7	12	12.7	751	1709@51	BW
225/65R17 102H	110101518	SL	600/A/B	30.3	6.5	6.0 - 8.0	8.9	28.5	6.7	12	13	728	1874@51	BW
235/65R17 108H	110101519	XL	600/A/B	32.1	7	6.5 - 8.5	9.3	29.1	7	12	13.2	713	2205@50	BW
235/70R17 109H	110101584	XL	600/A/B	34.6	7	6.0 - 8.0	9.4	29.8	7	13	13.5	696	2271@50	BW
P235/75R17 108T	110101520	SL	600/A/B	37	6.5	6.0 - 8.0	9.2	30.9	7	13	13.9	671	2205@51	OWL
LT235/80R17 120/117R	110101637	E	NA	46.5	6.5	6.00 - 7.50	9.2	31.9	7.2	17	14.3	651	3085@80	OWL
LT245/65R17 117/114S	110101680	E	NA	42.7	7	7.00-8.50	9.7	29.8	7.6	17	13.5	698	2835@80	OW
P245/65R17 105T	110101521	SL	600/A/B	35.1	7	7.0 - 8.5	9.6	29.6	7.2	12	13.4	702	2039@51	OWL
LT245/70R17 119/116R	110101638	E	NA	45.4	7	6.5 - 8.0	9.7	30.6	7.6	17	13.8	678	3000@80	OWL
P245/70R17 108T	110101522	SL	600/A/B	36.4	7	6.5 - 8.0	9.7	30.6	7.2	13	13.8	680	2205@51	OWL
LT245/75R17 121/118S	110101639	E	NA	47	7	6.5 - 7.50	9.6	31.7	7.6	17	14.2	656	3195@80	OWL
255/65R17 114H	110101578	XL	600/A/B	36.8	7.5	7.0 - 9.0	10.2	30.1	7.6	12	13.6	690	2601@50	BW
LT255/65R17 119/116S	110101682	E	NA	45.5	7.5	7.50-9.00	10.2	30.3	8	17	13.7	686	3000@80	BW
P255/70R17 110T	110101523	SL	600/A/B	37.3	7.5	6.5 - 8.5	10.1	31.2	7.6	13	14	666	2337@51	OWL
P255/75R17 113T	110101524	SL	600/A/B	40.7	7	6.5 - 8.5	10	32.1	7.6	13	14.4	647	2535@51	OWL
LT265/65R17 120/117R	110101678	E	NA	46.9	8	8.00-9.50	10.6	30.7	8.3	17	13.9	676	3085@80	OW
P265/65R17 110T	110101525	SL	600/A/B	37.5	8	7.5 - 9.5	10.5	30.7	8	12	13.8	677	2337@51	OWL
LT265/70R17 121/118S	110101640	E	NA	51	8	7.0 - 8.5	10.7	31.9	8.3	18	14.3	651	3195@80	OWL
LT265/70R17 121/118S	110133530	E	NA	50.5	7	7.0-8.5	10.3	31.9	8.3	18	14.3	651	3195@80	BW
LT265/70R17 121/118S	110277530	E	NA	50.4	8	7.00-9.00	10.7	31.9	8.3	18	14.3	651	3195@80	BW
P265/70R17 113T	110101526	SL	600/A/B	40.6	8	7.0 - 9.0	10.6	31.7	8	13	14.2	655	2535@51	OWL
275/65R17 115H	110101579	SL	600/A/B	40.5	8	7.5 - 9.5	10.9	31.1	8.1	12	14	667	2679@51	BW
285/65R17 116H	110101588	SL	600/A/B	41.4	8.5	8.0 - 10.0	11.5	31.5	8.5	13	14.2	659	2756@51	BW
LT285/70R17 121/118S	110101641	E	NA	55.2	8.5	7.50 - 9.00	11.4	32.8	8.8	18	14.7	633	3195@80	OWL
P285/70R17 117T	110101527	SL	600/A/B	45	8.5	7.5 - 9.5	11.3	32.8	8.5	13	14.7	633	2833@51	OWL
LT285/75R17 121/118S	110101642	E	NA	60.4	8	7.5 - 9.5	11.2	33.9	8.8	18	15.1	613	3195@80	OWL
LT315/70R17 121/118S	110101643	E	NA	61.2	9.5	8.0 - 11.0	12.4	34.4	9.8	18	15.3	604	3195@65	OWL