

ALL SIZES AND SPECS

TIRE SIZES BY WHEEL DIAMETER														
			15" 12 sizes	16" 24 sizes	17" 29 sizes	18" 22 sizes	19" 2 sizes	20" 18 sizes	22" 4 sizes					
TIRE SIZE	PART NUMBER	LOAD I.D.	UTQG RATING	UNIT WEIGHT (lbs.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (in.)	TREAD DEPTH (32/in.)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE	TYPE
					Meas.	Appr.	Overall Width	Overall Diameter			Static Radius	Rev / Mile	Single	
35X12.50R20 121R	110101651	E	NA	61.1	10	8.5 - 11.0	12.4	34.7	9.8	16	15.7	599	3195@65	BW
245/50R20 105H	110101677	XL	600/A/B	34.1	7.5	7.00-8.50	9.8	29.8	8.2	12	13.8	697	2039@50	BW
265/50R20 107H	110101620	SL	600/A/B	38.8	8.5	7.5-9.5	10.9	30.4	8.9	12	14	684	2149@51	BW
LT265/60R20 121/118S	110101652	E	NA	52.2	8	7.50 - 9.50	10.5	32.8	8.5	17	15	633	3195@80	BW
275/55R20 117H	110101534	XL	600/A/B	40.8	8.5	7.5 - 9.5	11.1	31.8	8.7	12	14.6	653	2833@50	BW
LT275/55R20 120/117S	110101653	E	NA	52.3	8.5	7.5 - 9.5	10.9	32.3	8.6	16	14.8	643	3085@80	BW
275/60R20 115H	110101535	SL	600/A/B	44.5	8	7.5 - 9.5	10.9	33.1	8.2	12	15.1	627	2679@51	BW
LT275/60R20 123/120S	110101654	E	NA	56.3	8	7.5 - 9.5	11.1	33.3	8.6	17	15.2	624	3415@80	BW
LT275/65R20 126/123R	110101655	E	NA	57.2	8	7.5 - 9.5	10.9	34.3	8.6	17	15.6	606	3750@80	BW
285/50R20 112H	110101590	SL	600/A/B	42.8	9	8.0 - 10.0	11.7	31.3	9.6	12	14.4	665	2469@51	BW
LT285/55R20 122/119S	110101656	E	NA	55.1	9	8.00 - 10.00	11.4	32.6	9.4	17	14.9	636	3305@80	BW
LT285/60R20 125/122S	110101657	E	NA	59.6	8.5	8.0 - 10.0	11.4	33.9	9.1	17	15.4	612	3640@80	BW
LT285/65R20 127/124S	110101658	E	NA	60.5	8.5	8.0 - 10.0	11.6	34.8	9	17	15.8	598	3860@80	BW
LT295/55R20 123/120S	110101622	E	NA	57.5	9.5	8.0-10.0	11.9	33	9.5	16	15.1	629	3415@80	BW
LT295/60R20 126/123S	110101659	E	NA	59.9	8.5	8.0 - 10.0	11.7	34.2	9.4	17	15.5	607	3750@80	BW
LT295/65R20 129/126S	110101660	E	NA	68.3	8.5	8.0 - 10.0	11.7	35.4	9.2	17	16	587	4080@80	BW
LT305/55R20 121/118S	110101661	E	NA	57.1	9.5	8.50 - 11.00	12	33.5	9.6	16	15.3	619	3195@65	BW
LT325/60R20 121/118S	110101662	D	NA	67.8	9.5	9.0 - 12.0	12.8	35.6	10.3	16	16.1	584	3195@50	BW